



12

EUROPÄISCHE PATENTANMELDUNG

21 Anmeldenummer: 89112564.3

51 Int. Cl. 4: H01H 71/10, H02H 3/02

22 Anmeldetag: 10.07.89

30 Priorität: 15.07.88 DE 3823975

43 Veröffentlichungstag der Anmeldung:
17.01.90 Patentblatt 90/03

94 Benannte Vertragsstaaten:
AT BE CH DE FR GB IT LI

71 Anmelder: Asea Brown Boveri
Aktiengesellschaft
Kallstadter Strasse 1
D-6800 Mannheim-Käfertal(DE)

72 Erfinder: Runtsch, Erhard
Karlsbader Strasse 17
D-6944 Hemsbach(DE)
Erfinder: Velten, Walter
Carl-Goerdeler Strasse 1
D-6830 Schwetzingen(DE)
Erfinder: Goehle, Rolf
Im Bubenwingert 16
D-6906 Leimen(DE)
Erfinder: Schmitt, Hermann
Im Vogelskorb 1
D-6803 Edingen-Neckarhausen(DE)
Erfinder: Greefe, Klaus
Hausserstrasse 55
D-6900 Heidelberg(DE)
Erfinder: Kymke, Dietmar
Maria-Probst-Strasse 15
D-6903 Neckargemünd(DE)

74 Vertreter: Rupprecht, Klaus, Dipl.-Ing. et al
c/o Asea Brown Boveri Aktiengesellschaft
Zentralbereich Patente Postfach 100351
D-6800 Mannheim 1(DE)

54 Selektive Kurzschlussstromschutzeinrichtung.

EP 0 350 829 A2

57 Selektiver Hauptsicherungsautomat

Bei bekannten selektiven Hauptsicherungsautomaten wird die Trennstelle im Hauptstrompfad periodisch geschlossen, wodurch bei einer Kurzschlussstromabschaltung in einem bestimmten Kurzschlussstrombereich daraus höhere Durchlaß- I^2t -Werte resultieren.

Diesem Problem wird abgeholfen dadurch, daß nach erfolgter Begrenzung des ersten Kurzschlußimpulses die Rückschließung der Hauptkontaktstelle erst bei Nennbetriebsverhältnissen erfolgt und von einer in einem parallel zum Hauptstrompfad geschal-

teten Nebenstrompfad befindlichen Selektivitätseinrichtung (33) zeitgesteuert ist.

Bevorzugtes Anwendungsgebiet des neuen selektiven Hauptsicherungsautomaten sind Niederspannungsverteilanlagen insbesondere Gebäudeinstallationen.




Fig. 1

DELPHION

Log Out

Work Files

Saved Searches

RESEARCH

My Account

PRODUCTS

INSIDE DELPHION

Select OR

No active trail

Select AND

Search:

Quick/Number

Boolean

Advanced

Derwent

Help

The Delphion Integrated View

Get Now: ☒ PDF ☐ More choices...

Tools: Add to Work File: ☐ Create new Work File

View: | | | | ☒ Email this to a friend

Title: **EP0350829B1: Selective protective device against short-circuit currents**[\[German\]](#)[\[French\]](#)

Derwent Title: Selective short-circuit current protection in distribution network - involves limitation of initial fault current pulse followed by main contactor reclosure using timed selectivity switch [\[Derwent Record\]](#)

Country: EP European Patent Office (EPO)

Kind: B1 Patent (See also: [EP0350829A2](#), [EP0350829A3](#))

Inventor: Runtsch, Erhard;
Velten, Walter;
Goehle, Rolf;
Schmitt, Hermann;
Greefe, Klaus;
Dymke, Dietmar;

Assignee: Asea Brown Boveri Aktiengesellschaft
[News](#), [Profiles](#), [Stocks](#) and [More](#) about this company

Published / Filed: 1995-11-29 / 1989-07-10


Application Number: EP1989000112564

IPC Code: H01H 71/10; H02H 3/02;

ECLA Code: H01H71/10F; H02H7/30;

Priority Number: 1988-07- DE19880003823975

Abstract: [From equivalent [EP0350829A2](#)] Selective automatic main circuit-breaker in known selective automatic main circuit-breakers, the disconnection point in the main current path is periodically closed, resulting in higher let-through values given a short-circuit



current disconnection in a given short-circuit current range. This problem is remedied, in that, after the first short-circuit pulse has been limited, the re-closing of the main contact point is carried out only given nominal operating conditions, and is time-controlled by a selectivity device (33) located in a shunt current path connected in parallel with the main current path. Preferred application area of the novel selective automatic main circuit-breaker are low-voltage distribution systems, especially building installations.

Attorney, Agent
or Firm:
INPADOC
Legal Status:
Designated
Country:

Rupprecht, Klaus, Dipl.-Ing. et al ;

Show legal status actions Get Now: Family Legal Status Report

AT BE CH DE FR GB IT LI

Family:

| PDF | Publication | Pub. Date | Filed | Title |
|------------------------------|------------------------------|------------|------------|--|
| | EP0350829B1 | 1995-11-29 | 1989-07-10 | Selective protective device against short-circuit currents |
| | EP0350829A3 | 1991-07-17 | 1989-07-10 | Selective protective device against short-circuit currents |
| | EP0350829A2 | 1990-01-17 | 1989-07-10 | Selective protective device against short-circuit currents |
| | DE58909512C0 | 1996-01-11 | 1989-07-10 | SELEKTIVE KURZSCHLUSSSTROMSCHUTZEINRICHTUNG. |
| | DE3823975A1 | 1990-01-18 | 1988-07-15 | Selective Kurzschlussstromschutzeinrichtung |
| | AT0130957E | 1995-12-15 | 1989-07-10 | SELEKTIVE KURZSCHLUSSSTROMSCHUTZEINRICHTUNG. |
| 6 family members shown above | | | | |

Description
Expand description

Die Erfindung betrifft einen selektiven Hauptsicherungsautomat gemäß dem Oberbegriff des Anspruchs 1.

+ 1. Einschalten auf Nennbetrieb

+ 2. Einschalten auf Leerlauf

+ 3. Einschalten auf Kurzschlußstrom

First Claim:



Show all claims 1. Selective main protective miniature circuit-breaker (10) for the selective disconnection of short-circuit current in electrical distribution networks which each have individually protected loads (14), the main protective miniature circuit-breaker being used for the selectively staggered protection of the loads (14)

of a load network against short-circuit currents and over-currents in a load (14), selectively with respect to the remaining loads (14), having a main current path (24) and having an auxiliary current path (34) which is connected in parallel therewith, having a main contact point (26) which is arranged in the main current path (24) and has at least one fixed and one movable contact element, having an electromagnetic instantaneous release (30) which is likewise arranged in the main current path (24) and cooperates with a main switching mechanism (28) which is connected to the movable contact element of the main contact point (26) and is operatively connected to a manual switching handle (42) and an overcurrent release (32) arranged in the main current path (24), and having in each case one incoming and one outgoing terminal (20, 22), characterized in that a latching device (29) is provided, in which the movable contact element (27), which is struck open as a result of a short circuit, of the main contact point (26) latches into place, in that the auxiliary current path (34) which is connected to the main current path (24) at the terminals (20, 22) has a selectivity device (33) which cooperates with the latching device (29), in that the selectivity device (33) which is excited by a short-circuit current brings about, in a time-controlled manner, the unlatching of the movable contact element, and in that there is arranged in the auxiliary current path (34) a second overcurrent release (38) which is connected in series with the coil (35), cooperates with the main switching mechanism (28) and, in the event of tripping due to a short-circuit current that is present, automatically brings about the opening of a further contact point (40) arranged in the auxiliary current path (34) as well as the further opening of the contact element (27) of the main contact point (26) right into the "off" position, as a result of which the load network (13) is isolated from the supply network (16).

[German] [French]

DERABS G90-016177

Other Abstract
Info:



Nominate this for the Gallery...



[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact Us](#) | [Help](#)

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.